

SIMREX Corporation DataMover™ 2070-TA ATC, ATSC or 2070 Controller Compatible

2070 Controller
Wireless / Wired
Modem Card



WIRELESS traffic CONTROL

CARD FEATURES

- Compatible with all ATC, ATSC and 2070 traffic controllers that have an H1 card slot. The H1 card is normally used for hosting a 6A or 7A card (serial or FSK modem)
- ZERO FOOT PRINT. Installs directly into controller communications board slot.
- No External Power Supply Required
- Electrically isolated from Chassis ground
- Electrically isolated coaxial RF connector for radio antenna
- An electrically isolated serial port is available to be port shared with the radio
- Second serial port has configurable routing for port sharing purposes
- Available 900 MHz or 2400 MHz

RADIO FEATURES

- Variable RF Output up to Maximum FCC Limit of 1W.
- License Free, Robust, Spread Spectrum Technology
- Forward Error Correction (FEC)
- Up to 25 Miles Range*
- Store and Forward Repeater Capability with Self Healing Networks.
- Transparent to all Asynchronous Protocols.
- Network Wide Data/Diagnostics Compatible with SIMREX DataMover SS Radios
- Separate Data and Diagnostics ports.

SIMREX..Global wireless solutions

For almost 3 decades, SIMREX Corporation's wireless products have been providing wireless networking solutions with applications in SCADA, telemetry, telecommunications, mobile data and online transaction markets. SIMREX Corporation provides licensed and unlicensed frequency solutions, installed worldwide.

Product Overview

SIMREX Corporation has created the DataMover 2070-TA by integrating its unparalleled DataMover SS spread spectrum wireless modem onto a 2070 Controller communications card. The 2070 Card form factor provides the ultimate in system integration flexibility in a high-speed, compact license-free wireless solution. The data and antenna connections are isolated from the controller chassis ground.

Why Consider a DataMover™ 2070-TA Solution?

- **Flexibility and rapid installation.** Quick return on investment due to "Plug and Play" installation, and no data or power wiring.
- **Electrical isolation of all data and RF connections** provides the ultimate in protection for the traffic controller.
- **Performance under the most adverse conditions.** Robust design provides excellent performance in the face of interference or difficult signal paths.
- **High system performance and data integrity.** Robust construction, digital signal processing (DSP) technology with adaptive equalization, automatic CRC/ARQ and powerful forward error correction (FEC).
- **"Zero" Footprint.** Fits in the place of the existing model 2070-6A, 2070-7 and 2070-7a communications cards.
- **2070 Network Functionality.** SIMREX DataMover 2070-TA implements HOST or Local 2070 network nodes with either MASTER, REMOTE or REPEATER radio configurations. Multiple repeaters can exist, preventing a single radio failure from disabling a network.
- **SIMREX network-wide diagnostic software** reduces the cost of managing the network infrastructure by eliminating trips to the field. Provides a non-intrusive means of maintaining link and network performance.
- **SIMREX DataMover 2070-TA is a price/performance leader** offering flexibility and reliability for all 2070 controller network topologies.

* with high gain antennas and clear RF line of sight.

DataMover™ 2070-TA Wireless Modem Card Specifications

Frequency Band 902-928 MHz ISM band

Physical and Environmental

Dimensions Standard 2070 Controller Comm. Card
(Approx. 8.92 D x 5.68 W x .80 H inches)
(Approx. 227 D x 144 W x 21 H cm)

Input Power Powered from 2070 Card Cage

Temperature Operating: -35° C to 75° C

Humidity 5% ~ 95% Typical
(non - condensing)

Transmitter

Power Output 1W (30 dBm) , user selectable lower power levels in 1 db increments.

Modulation CPFSK

Receiver

Sensitivity -110 dBm (1 x 10⁻⁶ BER) typical

Error Detection CRC16; Resend on Error

Interference Avoidance 64,000 hop patterns selected automatically via network address

FEC, CRC/ARQ and/or Multiple Packet Transmits

Excellent Strong Signal (interference) Characteristics

Band Partitioning for Friendly Coexistence with Other Services such as LMS

Data

Interface RS-232 and 2070 Controller backplane.

Usable Throughput 115.2 kbps

Port Speeds 1.2 to 115.2 kbps

Ethernet Option

Connectors (All Electrically Isolated)

Power (2070 backplane), Diagnostics (RJ11), Diagnostic data (DB9), RF(TNC)

Operating Modes

Point-to-Multipoint

Master

Remote

Repeater Extension (Store and Forward)

- Unlimited repeaters

- self healing networks

Network Management

Diagnostics, Spectrum Analyzer

Centralized network control eliminates site visits

Create store-and-forward configurations

Compatible with other SIMREX DataMover products

Agency Approvals

FCC

Part 15 Approved

Industry Canada

Approved

Applications

- Broken Copper Line Bridging
- Existing System Wireless / Wired Expansion.

SIMREX CORPORATION

SALES & ENGINEERING

GILBERT, ARIZONA 85234 USA
PHONE (480) 926-6069
FAX (305) 675-7794

WWW.SIMREX.COM

MANUFACTURING & SERVICE

1223 WILLIAM ST.
BUFFALO, NEW YORK 14206 USA
PHONE (716) 206-0174
FAX (716) 852-1223

SIMREX DataMover products are manufactured under a quality system certified to ISO 9001. SIMREX reserves the right to make changes to specifications of products described in this data sheet at any time without notice and without obligation to notify any person of such changes.
© 2004 SIMREX Corporation

2131015